



Big Voice Processing for Small Business

Managing voice message processing is a key component of your telephone system. The Strategy IVP8 voice processing system integrates with the Strata CIX™ business communication system to provide:

- Automated Attendant to answer incoming calls
- Call Routing to direct calls to the person or department the caller wants
- Telephone Answering to take messages when an employee is unavailable
- Voice Messaging to create, send, receive, forward, and save voice messages
- Audiotext to play pre-recorded information on demand
- Call Screening to announce the calling party
- Message Notification to let users know when a voice message arrives
- Unlimited Mailboxes to accommodate as many as your application requires

Strategy™ voice processing gives you the ability to:

- Simplify voice mailbox operation through an intuitive user interface
- Record calls directly into your voice mailbox with a single button on your telephone
- Communicate effectively both in and out of the office with other employees and customers
24 hours-a-day, 365 days-a-year

Customize voice processing functions using Strategy's Token Programming, a powerful yet simple scripting language. Tokens can add or enhance voice mail features and functions such as recording and playback, audio files, or using DTMF entries by callers to provide data response or special call routing. Tokens can perform functions as simple as a hook-flash, and as complicated as an IVR application, specific to your needs. Token Programming is developed and deployed by Authorized Toshiba Dealers.

The Strategy IVP8 integrates voice message processing on a single printed circuit card inside the Strata CIX chassis. Because there is no need for external connections, standard telephone ports, or separate power backup systems, the IVP8 decreases the cost and complexity of deploying voice mail applications.

SPECIFICATIONS

Model	Stratagy IVP8				
Capacities	Minimum configuration 2 ports, expandable to 4, 6, or 8 ports via electronic upgrade. Message storage 15 hours, upgradeable to 30 hours. Unlimited mailboxes.				
Chassis Measurements	Width	Height	Depth	Weight	
	Metric	33 mm	191 mm	152 mm	.4 kg
	English	1.3 in.	7.5 in.	6 in.	.8 lbs.
Power Supply Unit (PSU)	Uses hosting Strata CIX power supply				
Primary AC Power	Input AC 120VAC, 4.0 amps maximum. AC Frequency Single-phase (48Hz - 62Hz).				
Power Backup	Provided by the power backup of the hosting Strata CIX chassis				
Cooling	Convection				
Operating Temperature	39~104° F (4~40° C)				
Operating Humidity	20~80% relative humidity without condensation				
Storage Temperature	-4~140° F (-20~60° C)				
Chassis Installation	Printed circuit board installs in card slot in Strata CIX100, CIX200, or CIX670 chassis.				
Compliance	Safety: UL EMC: FCC Part 15 Class A (Subpart J)				
Data Storage Media	Compact Flash 256MB, upgradeable to 512MB				
CPU	Embedded				
Memory	4MB				
Operating System	ROM DOS				
Voice Resources	On-board (8 channels maximum)				
Modem	Internal soft modem 14.4k baud				
Communication Ports	Two RS-232 COM ports				
Connection to Strata CIX	Direct backplane in slot in Strata CIX chassis				
Remote Access	Modem				
Standard Applications	Stratagy Voice Mail, Auto Attendant, Token Programming.				
Optional Applications	IVR capabilities available via Token Programming or custom development.				
Application Installation	Deployed by Authorized Toshiba Dealers.				

Toshiba America Information Systems, Inc., Telecommunication Systems Division

9740 Irvine Blvd., Irvine, CA 92618-1697 (949) 583-3700 www.telecom.toshiba.com

© 2006 Toshiba America Information Systems, Inc., Telecommunication Systems Division. Printed in U.S.A. Strata is a registered trademark of Toshiba Corporation. Stratagy is a registered trademark of Toshiba America Information Systems, Inc. Specifications subject to change without notice. Some features require optional hardware/software to support full capabilities.

Literature Order #: TSD-CIX-BR-IVP8-DS-VA/4500044